according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2023
002	07/29/2024	NSK-SDS-008-EU(EN)	Date of first issue: 08/23/2018

#### SECTION 1. IDENTIFICATION

Product name : Perio Mate Powder

Manufacturer or supplier's details						
:	NAKANISHI INC. Quality Assurance Dept.					
	Quality Assurance Dept.					
:	700 Shimohinata					
	Kanuma-shi Tochigi, Japan 322-8666					
:	+81(0)289-64-3380					
:	+81(0)289-62-5636 (8:00-17:00,JST)					
hen	nical and restrictions on use					
:	Surface treatment					
	: : : hen					

: Not applicable

### SECTION 2. HAZARDS IDENTIFICATION

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Restrictions on use

#### **GHS** label elements

Signal Word	:	Warning
Hazard Statements	:	May form combustible dust concentrations in air.

#### Other hazards

Dust contact with the eyes can lead to mechanical irritation. Contact with dust can cause mechanical irritation or drying of the skin.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	68909-20-6	1

#### **SECTION 4. FIRST AID MEASURES**

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Versic 002	n Revision Date: 07/29/2024	SDS No NSK-S	umber: DS-008-EU(EN)	Date of last issue:11/20/2023 Date of first issue: 08/23/2018	
Ge	eneral advice	:	vice immediately.	dent or if you feel unwell, seek medical ad- ersist or in all cases of doubt seek medical	
lf i	nhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.		
In	In case of skin contact		Wash with water ar Get medical attenti	nd soap. on if symptoms occur.	
In	In case of eye contact		lf in eyes, rinse wel Get medical attenti	l with water. on if irritation develops and persists.	
lf s	If swallowed			OT induce vomiting. on if symptoms occur. ughly with water.	
an	Most important symptoms and effects, both acute and delayed		the skin.	an cause mechanical irritation or drying of ne eyes can lead to mechanical irritation.	
Pr	otection of first-aiders	:	No special precauti	ons are necessary for first aid responders.	
No	tes to physician	:	Treat symptomatica	ally and supportively.	

#### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Do not use a solid water stream as it may scatter and spread fire. Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides Nitrogen oxides (NOx) Silicon oxides
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Version 002	Revision Date: 07/29/2024	SDS Nu NSK-S	umber: DS-008-EU(EN)	Date of last issue: 11/20/2023 Date of first issue: 08/23/2018
	cial protective equipr re-fighters	nent :	Wear self-contained b necessary. Use personal protecti	preathing apparatus for firefighting if ve equipment.
SECTION	6. ACCIDENTAL F	RELEASE	MEASURES	
tive e	onal precautions, pr equipment and emer cy procedures		-	advice (see section 7) and personal pro- ommendations (see section 8).
Envi	ronmental precaution	ns :	Retain and dispose of	environment. ge or spillage if safe to do so. f contaminated wash water. Ild be advised if significant spillages
	nods and materials fo ainment and cleaning		tainer for disposal. Avoid dispersal of dus with compressed air). Dust deposits should ces, as these may for sed into the atmosphe Local or national regu sal of this material, as ployed in the cleanup which regulations are	f this SDS provide information regarding

#### SECTION 7. HANDLING AND STORAGE

Technical measures	:	Static electricity may accumulate and ignite suspended dust causing an explosion. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Do not breathe dust. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	:	Keep in properly labeled containers. Store in accordance with the particular national regulations.

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Version 002	Revision Date: 07/29/2024	SDS Number: NSK-SDS-008-EU(EN		of last issue: 11/20/20 of first issue: 08/23/20	
Mater	ials to avoid	: Do not store v Strong oxidizi	with the following	product types:	
SECTION	8. EXPOSURE CO	ONTROLS/PERSONAL	PROTECTION		
Ingre	dients with workp	lace control paramete	ers		
inert o	or nuisance dust			oot :TWA (total dust)	
		15 mg/m³ Value type (Fo Basis: OSHA 2	• •	: TWA (total dust)	
		5 mg/m³ Value type (Fo Basis: OSHA 2		: TWA (respirable fra	ction)
		•		oot : TWA (respirable fra	ction)
Dust, ticula	nuisance dust and tes		• •	: PEL (Total dust)	
		5 mg/m³ Value type (Fo Basis: CAL PE		: PEL (respirable dus	t fraction)
Comp	oonents	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
(trime	amine, 1,1,1-trimeth thylsilyl)-, hydrolys cts with silica		TWA (Dust)	20 Million par- ticles per cubic foot (Silica)	OSHA Z-3
			TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3

(Silica)

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.

TWA

(Silica)

6 mg/m<sup>3</sup>

NIOSH REL

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Version 002	Revision Date: 07/29/2024	SDS Nu NSK-SI	mber: DS-008-EU(EN)	Date of last issue: 11/20/2023 Date of first issue: 08/23/2018	
			Apply measures to Ensure that dust-h dust collectors, ver signed in a manne	e exposure concentrations. o prevent dust explosions. andling systems (such as exhaust ducts, ssels, and processing equipment) are de- r to prevent the escape of dust into the ere is no leakage from the equipment).	
Perso	nal protective eq	uipment			
Respiratory protection :		:	General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazar- dous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.		
Hand	protection				
Ma	aterial	:	Chemical-resistant	gloves	
Re	marks	:		epeated contact use protective gloves. e breaks and at the end of workday.	
Eye p	rotection	:	Wear the following Safety goggles	personal protective equipment:	
Skin a	and body protection	ı :	Skin should be wa	shed after contact.	
Hygier	ne measures	:	eye flushing syste king place. When using do no	mical is likely during typical use, provide ms and safety showers close to the wor- t eat, drink or smoke. ed clothing before re-use.	

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	white
Odor	:	odorless
Odor Threshold	:	No data available

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

pH:No data availableMelting point/freezing point:< 451 °F / < 233 °CInitial boiling point and boiling range:No data available	
Initial boiling point and boiling : No data available	
Flash point : Not applicable	
Evaporation rate : Not applicable	
Flammability (solid, gas) : Not classified as a flammability hazard	
Upper explosion limit / Upper : Not applicable flammability limit	
Lower explosion limit / Lower : Not applicable flammability limit	
Vapor pressure : Not applicable	
Relative vapor density : Not applicable	
Relative density : < 1.16 (68 °F / 20 °C)	
Solubility(ies) Water solubility : soluble	
Partition coefficient: n- : Not applicable octanol/water	
Autoignition temperature : Not applicable	
Decomposition temperature : < 536 °F / < 280 °C	
Viscosity Viscosity, kinematic : Not applicable	
Explosive properties : Not explosive	
Oxidizing properties : The substance or mixture is not classified as oxidizing.	
Particle size : No data available	

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Versior 002	n Revision Date: 07/29/2024	SDS Nu NSK-S	umber: DS-008-EU(EN)	Date of last issue: 11/20/2023 Date of first issue: 08/23/2018
Pos	sibility of hazardous s	reac- :		n explosive mixture in air. trong oxidizing agents.
Cor	nditions to avoid	:	Avoid dust forma	ation.
Inco	ompatible materials	:	Oxidizing agents	3
	ardous decompositio ducts	n :	No hazardous d	ecomposition products are known.

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

#### Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 423
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

#### Skin corrosion/irritation

Not classified based on available information.

#### Components:

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

#### Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2023
002	07/29/2024	NSK-SDS-008-EU(EN)	Date of first issue: 08/23/2018

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

#### Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

#### Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
		Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
		Test Type: Chromosome aberration test in vitro Result: negative

#### Carcinogenicity

Not classified based on available information.

- **IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- **NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### **Reproductive toxicity**

Not classified based on available information.

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2023
002	07/29/2024	NSK-SDS-008-EU(EN)	Date of first issue: 08/23/2018

#### Aspiration toxicity

Not classified based on available information.

#### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

#### Components:

	rimethylsilyl)-, hydrolysis products with silica: LL50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other : aquatic invertebrates	EL50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 24 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic : plants	EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Persistence and degradability No data available	
Bioaccumulative potential No data available	

### Mobility in soil

No data available

#### Other adverse effects

No data available

#### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	<ul> <li>Empty containers should be taken to an approved waste handling site for recycling or disposal.</li> <li>If not otherwise specified: Dispose of as unused product.</li> </ul>

according to the OSHA Hazard Communication Standard

### **Perio Mate Powder**

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2023
002	07/29/2024	NSK-SDS-008-EU(EN)	Date of first issue: 08/23/2018

#### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

**UNRTDG** Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code** Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

**49 CFR** Not regulated as a dangerous good

### Special precautions for user

Not applicable

#### SECTION 15. REGULATORY INFORMATION

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

Denneylyania Dight To Ku	
US State Regulations	
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
SARA 311/312 Hazards	: Combustible dust

Pennsylvania Right To Know

Glycine


56-40-6

#### SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard

### Perio Mate Powder



#### Full text of other abbreviations

CAL PEL	:	California permissible exposure limits for chemical contami- nants (Title 8, Article 107)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
CAL PEL / PEL	:	Permissible exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office

according to the OSHA Hazard Communication Standard

### Perio Mate Powder

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2023
002	07/29/2024	NSK-SDS-008-EU(EN)	Date of first issue: 08/23/2018

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/

Revision Date : 07/29/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8